



TRUST OF BUILDING SOLUTIONS

ECONOMICAL UNIFORM COLOUR HARD & DURABLE WEATHER RESISTANT NON SHINKING NON CRACKING

SANDED CEMENTITIOUS GROUT For Tile Joints 4-15mm - Store in a dry Place



DIRECTION



















COVERAGE

Approximate coverage per 1 kg of Sanded Cementitious Grout

Tile Size (in mm)	Joint Width			
	4mm	8mm	10mm	12mm
100x100x8	152	82	69	59
200x200x8	239	124	100	84
300x300x10	350	180	146	123
400x400x10	470	139	483	152
450x450x10	528	258	214	181
300x450x12	351	178	145	121
600x300x12	391	198	159	133
600x600x12	582	294	235	188

MIXING:

Use FLEXE GD GROUT ADMIX Or Water 1.2 to 2.5 Ltr For 15Kg FLEXE CSG Gradually add in to water / Flexe Grout Admix for optimum result.

LIMITAIONS:

Do not use for tile with grout joint larger than 6mm. Do not use where chemical resistance is required. Do not use acied to clean joints.

SHELF LIFE:

Factory Sealed containers of this product are guaranteed for 1 years if stored dry area

PACKAGE

15 Kg Bag / Pail

Colour

Refer FLEXE CG Shade Card

CAUTION*

Contains portland cement, avoid contact with eyes Keep Reach out of children's





Product Name: FLEXE CSG

Shade Name : WHITE

Batch No : FIPL/CSG/010

Packed on : July 2022

MRP : ₹1275.00

Net Weight : 15Kg





FLEXECRETE INDIA PRIVATE LIMITED.,

No.91/3, Pillaiyar Kovil Street, Pandur Village, Kannivakkam, Guduvanchery- 603202. Tamil Nadu, India.

Mobile: +91 7010 007117 / 9344 600693

e-mail: info@flexecrete.com **Web:** www.flexecrete.com