

FLEXE SBR PLUS

MULTIPURPOSE BONDING AGENTS FOR CONCRETE AND MORTAR

SLURRY BOND COAT / WATERPROOFING SLURRY / FOR MORTAR AND SCREEDS

- Mix 1.5 volume of cement to FLEXE SBR PLUS by weight of cement.
- Mix to a lump-free creamy, consistency for 2-3 minutes by slowly adding of FLEXE SBR PLUS
- As water proofing slurry: Mix 2 parts cement to 1 part FLEXE SBR PLUS by weight of cement.
- For Repair Mortar: 1 Litre of FLEXE SBR PLUS and 5kg of Cement:15 kg of sieved sand and 1 litres of water.
- Using a stiff brush, work the bonding slurry well into the damp surface. When the bond coat is tacky apply mortar/screed overlay
- For Floor Topping/Screed. 1 Litre of FLEXE SBR PLUS 5Kg of Cement: 7.5Kg of sand and 7.5 kg of coarse aggregate small size less than 6mm and 1 litres of water.

Mixing Process Mortar/Screed:

- Use lump free cement, well graded sand/aggregates free of excessive fines. Mix sand, cement and coarse aggregate into mixer for 1-2 minutes. Hand mixing is only permissible when the total weight of the mix is less than 23kg.
- Mix required quantity of Flexe SBR Plus and water for 2 minutes in a separate container, to avoid excessive air entrapment. Finally, without delay, add the liquid mix slowly into the mixer containing the mixed powdered sand/coarse aggregate and cement until the required consistency is achieved.
- Vertical surfaces: Apply the bonding slurry to the prepared surface and then apply the FLEXE SBR PLUS render onto the wet bonding slurry. Application Thickness: 5 to 25mm.
- Screeds and toppings, applied to horizontal surfaces : Application thickness 10mm to 40mm. The FLEXE SBR PLUS modified mix should be placed over the still wet bonding slurry, well compacted by hand and trowelled to finish using a wooden float or steel trowel.

Packaging:

- 1 Litre
- 5 Litre
- 20 Litre



MANUFACTURED & PACKED BY:
FLEXECRETE INDIA PRIVATE LIMITED.,
No.91/3, Pillaiyar Kovil Street, Pandur Village, Kannivakkam,
Guduvanchery - 603202. Tamil Nadu, India.
Customer Care : +91 9344600693
e-mail: info@flexecrete.com, Web: www.flexecrete.com



FLEXE SBR PLUS

MULTIPURPOSE BONDING AGENTS FOR CONCRETE AND MORTAR



ADVANTAGES

- ✓ Improved tensile and flexural properties
- ✓ Excellent bond to concrete, masonry,
- ✓ Excellent bonds to Old and New concrete
- ✓ Excellent resistant to freeze/thaw
- ✓ Single product multipurpose uses for concrete cement mortars
- ✓ Ideal solution for concrete and mortar repair and patch works
- ✓ Ideal for making floor screeds in internal and external
- ✓ Increase excellent workability and good durable surfaces
- ✓ User friendly

DIRECTION FOR USE



Clean the surface and remove any dust, unsound or contaminated material, plaster, oil, paint, grease, corrosion deposits or algae.



Saw cut the concrete areas to a square or rectangular profile to a minimum 10mm depth at the extreme edges. Roughen the surface free of loose particles and dust and saturate with water. Remove excess/standing water.



Where breaking out is not required, roughen the surface and remove any laitance by light scabbling or grit-blasting.